

Wood

TECHNICAL DATA

Thermic Power (at min-at max)	kW	0,0 - 7,5
Introduced thermal power (at max)	kW	9,5
Water useful power (at min-at max)	kW	- -
Seasonal energy efficiency	η_s [%]	73
Useful efficiency (at min-at max)	%	0 - 83
Heating surface (at min-at max)	m ²	0 - 79
CO ₂ (min-max)	%	0,0 - 9,2
Emissions CO (13% O ₂) (at min-at max)	mg/Nm ³	0 - 916
Emissions OGC (13%O ₂) (at min-at max)	mg/Nm ³	0 - 29
Emissions NOX (13% O ₂) (at min-at max)	mg/Nm ³	0 - 95
Dust content at 13% O ₂ (at min-at max)	mg/Nm ³	0 - 27
Combustible Legna	mm	max L 330
Hopper capacity	kg	0
Hourly consumption (at min-at max)	kg/h	0,0 - 2,2
Autonomy (at min-at max)	h	0 - 0
Ignition electrical absorption (at max)	W	0
Operating electrical absorption (at max)	W	0
Chimney flue depression (at min-at max)	Pa	0 - 12
Mass of smoke (at min-at max)	g/sec	0,0 - 6,9
Exhaust fumes temperature (at min-at max)	°C	0 - 264
Distance from material comb. (back/side/under)	mm	40 / 2,5 / 0
Distance to material comb. (front/top)	mm	1000 / 750
Exhaust fumes outlet (A)	Ø mm	140
Combustion air inlet (B)	Ø mm	80
Ducting outlet (C)	Ø mm	0
Ductable up to	m	0

PLUS



Cooking



View on the Oven



Refractory stone



Ventilation + Light kit (optional)



Upper and back exhaust



Built-in

AVAILABLE FINISHES

71220017		Stainless Steel	EAN 8053859016380
71220018		Steel Anthracite	EAN 8053859016397
71220020		Steel Black	EAN 8053859016410

OPTIONAL

5021005	CONNECTOR PIPE 140-150MM	EAN 8053859014256
---------	--------------------------	-------------------

CERTIFICATIONS


European standards
Art. 15A B-VG 2015
BImSchV 2015
Regensburg
München
Stuttgart
Aachen



EN 12815:2001/
A1:2004/AC:2007



STOVE PACKAGE



L (cm)	H (cm)	P (cm)
80	103	98
Volume (m ³)	0,81	
Gross weight (kg)	162.8	
Net weight (kg)	147.2	

STORAGE



N° (max)
1

TRANSPORT



39 pz